




NTN BEARING-SUDAMERICANA, S.A.



NKX20T2Z Bearing 2D drawings and 3D CAD models

NTN NKX20T2Z Complex bearing

Bearing No. NKX20T2Z

Bore Diameter	20 mm
Outer Diameter	36 mm
d	20 mm
Fw	20 mm
D	30 mm
D1	35 mm
D2	36 mm
C	30 mm
a	30,7 mm
r min.	0,3 mm
C1	10 mm
da min.	29 mm
ra max.	0,3 mm
C2	10,5 mm
Weight	0,09 Kg
Dynamic load rating radial (C)	16,4 kN
Dynamic load rating axial (C)	14,2 kN
Static load rating radial (C0)	27,1 kN
Static load rating axial (C0)	24,7 kN
(Grease) Lubrication Speed	5200 r/min
dw	20 mm
rs min	0.3 mm
Dw	2 mm
Dw1	5.56 mm
Lw	15.8 mm



NTN BEARING-SUDAMERICANA, S.A.

Lubrication hole on outer ring	Oui/Yes
k	2.5 mm
Precision class	P0
Mass	0.09 kg
Cr	16.4 kN
Ca	14.2 kN
C0r	27.1 kN
C0a	24.7 kN
Nlim (grease)	5,200 rpm
Nlim (oil)	7,500 rpm
Min operating temperature, Tmin	-20 ° C
Max operating temperature, Tmax	120 ° C
da min	29 mm
ras max	0.3 mm
Category	Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.087
EAN	4547359126204
Product Group	B04144
bore diameter:	1.1811 in
radial static load capacity:	27100 N
outside diameter:	1.8504 in
bearing material:	High Carbon Chrome Steel
overall width:	1.1811 in
closure type:	Open
operating temperature range:	-40 to 250 ° F ° F
cage material:	Steel



NTN BEARING-SUDAMERICANA, S.A.

radial dynamic load capacity:	16400 N
manufacturer upc number:	4547359126204