



NTN BEARING-SUDAMERICANA, S.A.

3SRS9XM+[32-1000/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 3SRS9XM+[32-1000/1]L[H,P]M

3SRS9XM+[32-1000/1]L[H,P]M
drawings and 3D CAD models

Bearing 2D

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	3
Nominal Part Number	9
Rail Type	Standard
Rail Width W1	9 mm
Mounting Height M	10 mm
Rail Length L	32 ~ 1000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	2690
Basic Load Rating Static Rating Co(N)	2750
Allowable Static Moment MA(N m)	9.31
Allowable Static Moment MB(N m)	10.7
Allowable Static Moment MC(N m)	12.7
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	20 mm
Block external dimension L	30.8 mm
Number of Block Mounting	4



NTN BEARING-SUDAMERICANA, S.A.

Holes(holes)	
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	19.8 mm